

## CT4E

### Fully Automatic Random Four Edge Carton Sealer

The BestPack™ CT4E Series is a fully automatic random four outer edge carton sealer. These sealers are designed to eliminate costly hand taping of the four outer edges of randomly sized cartons where pilfer proofing and protection of your product from outside environment is necessary. The unit includes a front side entry for a 90 degree directional carton turn before entering into the four edge sealing station.

The CT4E line incorporates our exclusive 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



Above unit shown is right side infeed. Front infeed protection on the left is an available option at additional cost.

## Key Points of the Carton Sealer



**No Operator  
Required**



**Random Cartons**



**4-Edge Seal**

## Features

- Heavy Duty 3mm Welded Frame
- Seals All Four Outside Carton Edges Including All Corners
- Random Width and Random Height Adjustment
- 90 Degree Carton Turn Using Front Side Carton Infeed
- Top and Bottom Four Belt Drive System with 1-piece Molded Belts and V-belt Guide
- Includes Four 3" BestPack Pop-out High Speed Tape Heads
- Low Tape/No Tape on Carton/No Cut Sensors with Malfunction Alarm and Three-Colored Light
- Heavy Duty Upper Assembly Four Post System
- Uses Heavy Duty SMC Oil-less Cushioned Air-Cylinder
- Allen-Bradley PLC Logic
- Interlock Safety Gates Where Needed

- Tape Roll Lengths: 1,000 yd.
- Quality UL Approved Electrical Parts

## Options

- Spare Parts Kit
- Available in Either a Left Side Infeed or a Right Side Infeed (Side Infeed Turns Carton 90 Degrees for Edge Seal Carton Position)
- Food Grade 304 Stainless Steel

# Extra Accessories to Improve Efficiency



Carton Sealing Tape



Spare Tape Head

## Machine & Carton Specifications

**110 Volts 60 Hz**

Power Requirements

**Up to 5 Cartons/min.**

Speed

**100 PSI, 10+ SCFM**

Air Requirements

**(4) Four 3" BestPack**

Tape Heads

Model	Machine Dimensions Length x Width x Height	Carton Range Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
CT4EL22-3 <b>3" Tape Head</b> Left Side In-Feed	(98.43") x (53.15") x (67.32")	(11.81" - 23.62") x (9.84" - 23.62") x (9.84" - 23.62")	Determined at the time of order	Up to 5	1,470
CT4ER22-3 <b>3" Tape Head</b> Right Side In-Feed	(98.43") x (53.15") x (67.32")	(11.81" - 23.62") x (9.84" - 23.62") x (9.84" - 23.62")	Determined at the time of order	Up to 5	1,470

Information subject to change without notice.

All Models available in High Speed & Food Grade 304 Stainless Steel